





















## 100mm Thermoplastic Rubber Castors with Brake

### 100-3360-MGR/SWB

This Rubber Caster Wheel is 100mm diameter and made of Thermoplastic Rubber with a bonded on polypropylene wheel centre. This bonded rubber castor can take higher loads compared to a standard rubber wheel and the bonding process prevents tyre shear. With all the benefits of a non marking grey rubber wheel this castor is more competitively priced, hard wearing and longlasting. The easy foot operated brake locks the swivel and wheel into position.



### Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	88 shore A
	Load Capacity (kg)	100
	Manufacturer Part No.	TSZ7 MGR 100/30 P2 BP
	Max Load Capacity of 4 Castors	300
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	91
	Temperature Range	-20 min to +60 max
	Thread Material	No
	Total Castor Height	128
	Tread Width (mm)	30
	Wheel Centre	Grey Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	100
	Wheel Material	Rubber

### Dimensions

