





















100mm Swivel Polyurethane Castor Red Wheel

100-3360-PNB

This 100mm polyurethane castors are made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castor, with the red polyurethane wheel is strong and durable and suitable for moving machinery and equipment. The red polyurethane tire is bonded onto the polyamide nylon center making the castor very strong and durable. 3470UAR100P62 red 787-1391



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D60
	Load Capacity (kg)	200
	Manufacturer Part No.	TSZ7 NPR 100/30 P2
	Max Load Capacity of 4 Castors	600
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	91
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	128
	Tread Width (mm)	30
	Wheel Centre	White Polyamide
	Wheel Colour	Maroon
	Wheel Diameter(mm)	100
	Wheel Material	Polyurethane

Dimensions

