
















## 125mm Thermoplastic Rubber Castors

### 125-3360-MGR

This Rubber Caster Wheel is 125mm diameter and made of Thermoplastic Rubber with a bonded on polypropylene wheel centre. This bonded rubber castor can take higher loads compared to a standard rubber wheel and the bonding process prevents tyre shear. With all the benefits of a non marking grey rubber wheel this castor is more competitively priced, hard wearing and longlasting.



### Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	88 shore A
	Load Capacity (kg)	150
	Manufacturer Part No.	TSZ7 MGR 125/30 P2
	Max Load Capacity of 4 Castors	450
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	103
	Temperature Range	-20 min to +60 max
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	40
	Wheel Centre	Grey Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	125
	Wheel Material	Rubber

### Dimensions

