





















125mm Blue Rubber Castors with Brake - 4541038

125-3360-RNB/SWB

This 125mm braked castors is made of a zinc plated housing which ensures the castors are robust enough and suitable for a variety of environments. The swivel castor, with the non marking blue rubber wheel and a brake is suitable for trolleys, equipment and general purposes. The non marking blue rubber wheel with roller bearings means the castor is quiet to move, will not mark the floor and will carry significant loads of 180kgs on each castor . The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. 3477UFR125P62BLUE



Technical Specifications

	Bearing Type	Roller
	Colour	Blue
	Hardness of Tread	A64
	Load Capacity (kg)	200
	Manufacturer Part No.	TSZ7 NER 125/40 P2 BP 5017
	Max Load Capacity of 4 Castors	540
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	123
	Temperature Range	-20 min to +80 max
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	34
	Wheel Centre	Black Polypropylene
	Wheel Colour	Blue
	Wheel Diameter(mm)	125
	Wheel Material	Rubber

Dimensions

