




















125mm Fixed Castor with a black Rubber Wheel with a Metal Centre

125-3368-MPVR

This 125mm diameter medium duty fixed castor, with a solid black rubber wheel, is ideal for a large variety of applications. A fixed castor, has a fixed metal frame that supports the rubber wheel, and does not allow the wheel to swivel, enabling controlled uni-directional movement. Fixed Castors are often teamed up with swivel castors on equipment and trolleys for a controlled movement. With a top plate for easy attachment, you can also purchase our M8 Bolts and M8 Nuts, which are ideal for attaching this fixed castor to your application.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	A80
	Load Capacity (kg)	90
	Max Load Capacity of 4 Castors	270
	Plate Dimension Length (mm)	101
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	N/A
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	37
	Wheel Centre	Metal
	Wheel Colour	Black
	Wheel Diameter(mm)	125
	Wheel Material	Rubber

Dimensions

