

125mm Apex Heavy Duty Swivel Braked Castors with Polyurethane Wheel

125-5000-APEX/SWB

Extra heavy duty castors made of pressed steel zinc plated, housing a 125mm polyurethane wheel mounted on an aluminium centre for added strength. Carrying loads of 362kg each these industrial castors run on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These lockable castors are suitable for a range of heavy duty applications. Overall height 164mm, 4 x M10 Bolt Fixing Plate for ease of attachment.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	362kg
	Max Load Capacity of 4 Castors	1086
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	148
	Technical PDF	125-5000-PAL-SWB.pdf
	Temperature Range	-20 min to + 60 max
	Thread Material	No
	Total Castor Height	164
	Tread Width (mm)	50
	Wheel Centre	Aluminium
	Wheel Colour	Yellow
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

Dimensions

