





















Heavy Duty Braked Castors 125mm Black Rubber Wheel

125-5000-HRT/SWB

These 125mm extra heavy duty castors load capacity 300kgs each, overall height 164mm 4 x M10 Bolt Fixing Plate, these 5" braked castors are made of a heavy duty pressed steel zinc plated, housing a solid rubber wheel mounted on an aluminum centre. This castor wheel runs on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel caster head and the wheel. These heavy duty braked castors are suitable for a range of heavy industrial applications.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A67
	Load Capacity (kg)	300
	Max Load Capacity of 4 Castors	900
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	148
	Temperature Range	-20 min to +85 max
	Thread Material	No
	Total Castor Height	164
	Tread Width (mm)	40
	Wheel Centre	Aluminum
	Wheel Colour	Black
	Wheel Diameter(mm)	125
	Wheel Material	Rubber

Dimensions

