

125mm Heavy Duty Fixed Castors














Polyurethane Wheel 500kg

125-5050-PAL

These 125mm extra heavy duty fixed castors, overall height 164mm, load capacity 500kgs each, 4 X M10 Bolt fixing plate. Heavy duty fixed castors are made of a heavy duty pressed steel zinc plated, housing a polyurethane wheel mounted on an aluminium centre. This fixed castor wheel runs on ball journal bearings, making the heavier loads easier to move. These castors are suitable for a range of heavy duty applications. Combine 4 castors to take 1.5tonne castors load capacity. Electro conductive version available, please contact the sales team.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	500
	Max Load Capacity of 4 Castors	1500
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Temperature Range	-20 min to + 60 max
	Thread Material	No
	Total Castor Height	164
	Tread Width (mm)	50
	Wheel Centre	Aluminium
	Wheel Colour	Yellow
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

Dimensions

