





















160mm Thermoplastic Rubber Castors

160-3360-MGR

This Rubber Caster Wheel is 160mm diameter and made of Thermoplastic Rubber with a bonded on polypropylene wheel centre. This bonded rubber castor can take higher loads compared to a standard rubber wheel and the bonding process prevents tyre shear. With all the benefits of a non marking grey rubber wheel this castor is more competitively priced, hard wearing and longlasting.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	88 shore A
	Load Capacity (kg)	200
	Manufacturer Part No.	TSZ7 MGR 160/40 P3
	Max Load Capacity of 4 Castors	600
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	135
	Temperature Range	-20 min to +60 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	40
	Wheel Centre	Grey Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	160
	Wheel Material	Rubber

Dimensions

