





















160mm Swivel Castors with Brake White Nylon Wheel

160-3360-NYB/SWB

This 160mm braked castors is made of a zinc plated housing which ensures the castors are robust and suitable for a variety of environments. The braked swiveling castors, with the white nylon wheel is strong robust and durable and suitable for moving machinery and equipment. The white nylon wheel contains roller bearings making it easier to move whilst maintaining core strength. The foot operated wheel brake on these castors simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D75
	Load Capacity (kg)	350
	Manufacturer Part No.	TSZ7 NSR 160/40 P3 BP
	Max Load Capacity of 4 Castors	1050
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	167
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	40
	Wheel Centre	White Polyamide
	Wheel Colour	White
	Wheel Diameter(mm)	160
	Wheel Material	Nylon

Dimensions

