










160mm Swivel Castor Red Polyurethane Wheel

160-3360-PNB

This 160mm polyurethane industrial caster wheel is made of a zinc-plated housing which ensures the castor is robust enough and suitable for a variety of environments. This swivel castor featuring a red polyurethane wheel is strong, durable and suitable for moving heavy machinery and equipment. The red polyurethane tyre is bonded onto the polyamide nylon centre making the castor run quietly. 787-1414



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D60
	Load Capacity (kg)	300
	Manufacturer Part No.	TSZ7 NPR 160/40 P3
	Max Load Capacity of 4 Castors	900
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	135
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	40
	Wheel Centre	White Polyamide
	Wheel Colour	Maroon
	Wheel Diameter(mm)	160
	Wheel Material	Polyurethane

Dimensions

