

## 160mm Swivel Braked Castor Black Rubber Wheel

## 160-3360-PVR/SWB

This 160mm braked castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castor, with the black rubber wheel and a brake is suitable for trolleys, equipment machinery and general purposes. The black rubber wheel with roller bearings means the castor is quiet and easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



## **Technical Specifications**

٥	Bearing Type	Roller
50	Colour	No
0	Hardness of Tread	A85
KG	Load Capacity (kg)	150
KG X4	Max Load Capacity of 4 Castors	450
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
W.	Plate Hole Diameter	10
6 <sup>10</sup> A	Dradust Tupe	Top Plate Castors
٥	Product Type	Top Plate Castors
<u>~</u>	Swivel Radius	167
₫	Swivel Radius	167
<b>₩</b>	Swivel Radius Temperature Range	167 -20 min to +80 max
	Swivel Radius Temperature Range Thread Material	167 -20 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	167 -20 min to +80 max No 200
	Swivel Radius  Temperature Range  Thread Material  Total Castor Height  Tread Width (mm)	167 -20 min to +80 max No 200 25
	Swivel Radius  Temperature Range  Thread Material  Total Castor Height  Tread Width (mm)  Wheel Centre	167 -20 min to +80 max No 200 25 Red Polypropylene
	Swivel Radius  Temperature Range  Thread Material  Total Castor Height  Tread Width (mm)  Wheel Centre  Wheel Colour	167 -20 min to +80 max No 200 25 Red Polypropylene Black

## **Dimensions**





