





















## 160mm Blue Elastic Rubber Castors with Brake 300kg

### 160-3360-RNB/SWB

These 160mm braked castors are made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castors, with the non marking blue rubber wheel and a brake is suitable for trolleys, equipment and general purposes. The non marking blue rubber wheel with roller bearings means the castor is quiet to move, will not mark the floor and will carry significant loads of up to 300kgs each. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



### Technical Specifications

	Bearing Type	Roller
	Colour	Blue
	Hardness of Tread	A70
	Load Capacity (kg)	300
	Manufacturer Part No.	TS27 NER 160/45 P3 BP 5017
	Max Load Capacity of 4 Castors	900
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	167
	Temperature Range	-20 min to +80 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	40
	Wheel Centre	Black Polypropylene
	Wheel Colour	Blue
	Wheel Diameter(mm)	160
	Wheel Material	Rubber

### Dimensions

