

160mm High Temperature Castors with Brake & Phenolic Wheel

160-3360-TH/SWB

This 160mm medium duty swivel top plate braked castors with a termotex phenolic resin wheel suitable for medium/heavy duty applications, medical equipment, catering equipment and food manufacturing trolleys. The zinc plated castors are strong and durable and the termotex phenolic resin wheels are resistant to temperatures from -40C to +180C maximum. The foot operated brake simultaneously brakes both the swivel head and the wheel.



Technical Specifications

	Bearing Type	Plain
53	Colour	No
0	Hardness of Tread	D85
KG	Load Capacity (kg)	250
KG X4	Max Load Capacity of 4 Castors	750
(b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	Plate Dimension Length (mm)	137
<u> </u>	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
) i	Plate Hole Centres Width (mm)	80
W.	Plate Hole Diameter	10
٥	Product Type	Top Plate Castors
*	Product Type Swivel Radius	Top Plate Castors
3	Swivel Radius	170
<u> </u>	Swivel Radius Temperature Range	170 -40 min to + 180 max
	Swivel Radius Temperature Range Thread Material	170 -40 min to + 180 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	170 -40 min to + 180 max No 200
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	170 -40 min to + 180 max No 200 40
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	170 -40 min to + 180 max No 200 40 Black Phenolic Resin
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	170 -40 min to + 180 max No 200 40 Black Phenolic Resin Black

Dimensions





