

160mm Heavy Duty Swivel Castors Black Rubber Wheel

160-5000-HRT

These 160mm extra heavy duty rubber castors able to carry loads 400kgs each, combine 4 castors to carry over 1 tonne! Overall height 200mm, 4 x M10 Bolt Fixing Plate, these robust castors are made of a heavy duty pressed steel zinc plated, housing a 6" (160mm) solid rubber wheel mounted on an aluminum centre. This swiveling castor wheel runs on ball journal bearings, making the heavier loads easier to move. These castors are suitable for a range of heavy industrial applications.



Technical Specifications

| ٥ | Bearing Type | Ball Journal |
|--|--|---|
| 5 | Colour | No |
| 0 | Hardness of Tread | A67 |
| KG | Load Capacity (kg) | 400 |
| x4 | Max Load Capacity of 4 Castors | 1200 |
| | Plate Dimension Length (mm) | 140 |
| | Plate Dimension Width (mm) | 110 |
| | Plate Hole Centres Length (mm) | 105 |
| | Plate Hole Centres Width (mm) | 80/75 |
| W. | Plate Hole Diameter | 10 |
| | | |
| ٠ | Product Type | Top Plate Castors |
| <u>v</u> | Product Type Swivel Radius | Top Plate Castors |
| | | |
| 3 | Swivel Radius | 135 |
| <u>*************************************</u> | Swivel Radius Temperature Range | 135 -20 min to +85 max |
| | Swivel Radius Temperature Range Thread Material | 135 -20 min to +85 max No |
| | Swivel Radius Temperature Range Thread Material Total Castor Height | 135 -20 min to +85 max No 200 |
| | Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) | 135 -20 min to +85 max No 200 40 |
| | Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre | 135 -20 min to +85 max No 200 40 Aluminum |
| | Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour | 135 -20 min to +85 max No 200 40 Aluminum Black |

Dimensions

