

200mm Swivel Castor Red Polyurethane Wheel

200-3360-PNB

This 200mm polyurethane industrial castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. This swivel castor featuring a red polyurethane wheel is strong, durable and suitable for moving heavy machinery and equipment. The red polyurethane tire is bonded onto the polyamide nylon centre.



Technical Specifications

	Bearing Type	Roller
52	Colour	No
0	Hardness of Tread	D60
KG	Load Capacity (kg)	400
	Manufacturer Part No.	TSZ7 NPR 200/50 P3
KG X4	Max Load Capacity of 4 Castors	1200
	Plate Dimension Length (mm)	137
5 31	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
I	Plate Hole Centres Width (mm)	80/75
W.	Plate Hole Diameter	10
٥	Product Type	Top Plate Castors
	Product Type Swivel Radius	Top Plate Castors
O	Swivel Radius	155
C C	Swivel Radius Temperature Range	155 -40 min to +80 max
	Swivel Radius Temperature Range Thread Material	155 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	155 -40 min to +80 max No 240
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	155 -40 min to +80 max No 240 50
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	155 -40 min to +80 max No 240 50 White Polyamide
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	155 -40 min to +80 max No 240 50 White Polyamide Maroon

Dimensions



