

200mm Black Rubber Swivel Castor Wheel 200-3360-PVR


This 200mm swivel castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The castors, with a black rubber wheel, are suitable for trolleys, equipment, machinery and general purposes. The castors wheel with a black centre, contains roller bearings making the castor easier to move.




Technical Specifications

Ş	Bearing Type	Roller
5	Colour	No
0	Hardness of Tread	A85
KG	Load Capacity (kg)	200
Ka X4	Max Load Capacity of 4 Castors	600
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
No.	Plate Hole Diameter	10
Ô	Product Type	Top Plate Castors
15 15	Product Type Swivel Radius	Top Plate Castors
1		
3	Swivel Radius	155
	Swivel Radius Temperature Range	155 -20 min to +80 max
	Swivel Radius Temperature Range Thread Material	155 -20 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	155 -20 min to +80 max No 240
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	155 -20 min to +80 max No 240 33
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	155 -20 min to +80 max No 240 33 Red Polypropylene
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	155 -20 min to +80 max No 240 33 Red Polypropylene Black

Dimensions







Email: sales@rosscastors.co.uk

Ross Handling 1 Tuxford Road Leicester LE4 9TZ