




















## 200mm Fixed Nylon Castor Wheels

### 200-3368-NYB

This 200mm fixed castors is made of a zinc plated housing which ensures the castors are robust and suitable for a variety of environments. These fixed castors, with the white nylon wheel is strong robust and durable and suitable for moving machinery and equipment. The white nylon wheel contains roller bearings making it easier to move whilst maintaining core strength. Fixed castors can be teamed up with either swiveling castors and braked castors for maximum control when moving.



### Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D75
	Load Capacity (kg)	400
	Manufacturer Part No.	TSZ7 NSR 200/50 P3 FA
	Max Load Capacity of 4 Castors	1200
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	240
	Tread Width (mm)	46
	Wheel Centre	White Polyamide
	Wheel Colour	White
	Wheel Diameter(mm)	200
	Wheel Material	Nylon

### Dimensions

