





















200mm Heavy Duty Castors with Brake Polyurethane Wheel

200-5000-PAL/SWB

200mm extra heavy duty lockable castors made of heavy-duty pressed steel zinc. Housed in a polyurethane wheel and mounted on an aluminium centre for added strength. This 200mm polyurethane castor wheel runs on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These lockable castors are suitable for a range of heavy duty applications, carrying loads 800kg per castor wheel. Overall height 240mm, 4 x M10 Bolt Fixing Plate for easy attachment.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	800
	Max Load Capacity of 4 Castors	2400
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	160
	Temperature Range	-20 min to + 60 max
	Thread Material	No
	Total Castor Height	240
	Tread Width (mm)	50
	Wheel Centre	Aluminium
	Wheel Colour	Yellow
	Wheel Diameter(mm)	200
	Wheel Material	Polyurethane

Dimensions

