

200mm Heavy Duty Swivel Castors Polyurethane Aluminium Wheel 800kg

200-5000-PAL

These 200mm extra heavy duty polyurethane swivel castors made of a heavy duty pressed steel zinc plated, housing a polyurethane wheel on an aluminium centre. Each of these castors carry 800kgs each, overall height 240mm, 4 x M10 Bolt Fixing plate for easy attachment. This heavy duty swiveling castor wheel runs on ball journal bearings, making heavier loads easier to move. These castors are suitable for a range of heavy duty applications combine 4 of these castors to carry 2.4 tonnes castors.



Technical Specifications

	Bearing Type	Ball Journal
53	Colour	No
0	Hardness of Tread	A92
KG	Load Capacity (kg)	800
xq x4	Max Load Capacity of 4 Castors	2400
(h) (h)	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
7	Plate Hole Centres Width (mm)	80/75
W.	Plate Hole Diameter	10
٠	Product Type	Top Plate Castors
494	· · · · · · · · · · · · · · · · · · ·	•
Ü	Swivel Radius	155
3	Swivel Radius	155
	Swivel Radius Temperature Range	155 -20 min to + 60 max
	Swivel Radius Temperature Range Thread Material	155 -20 min to + 60 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	155 -20 min to + 60 max No 240
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	155 -20 min to + 60 max No 240 50
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	155 -20 min to + 60 max No 240 50 Aluminium
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	155 -20 min to + 60 max No 240 50 Aluminium Yellow

Dimensions





