





















## 200mm Heavy Duty Lockable Castors Polyurethane Wheel 800kg

### 200-5000-SUB/SWB

These 200mm extra heavy duty lockable castors are made of a heavy duty pressed steel zinc plated, housing a 200mm (8") polyurethane wheel mounted on a cast iron centre. This lockable castor wheel runs on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These lockable castors are suitable for a range of heavy duty applications, carrying loads of 800kgs each. Combine 4 lockable castors to carry 2.4 tonnes!



### Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	800
	Max Load Capacity of 4 Castors	2400
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	160
	Temperature Range	-40 min to + 60 max
	Thread Material	No
	Total Castor Height	240
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	200
	Wheel Material	Polyurethane

### Dimensions

