

80mm Swivel Castor Red Polyurethane Wheel

80-3360-PNB MAROON

This 80mm red polyurethane industrial castor is made of a zinc-plated housing which ensures the castors are robust enough and suitable for a variety of environments. Load capacity per castor is 100kgs each, and overall height 108mm. This swivel caster featuring a red polyurethane wheel is strong as well as durable and suitable for moving machinery and equipment. The red polyurethane tyre is bonded onto the polyamide nylon centre making the castor run quietly. Easily attached via the 4 x M8 fixing the top plate to your equipment.

787-1385



Technical Specifications

	Bearing Type	Roller
59	Colour	No
0	Hardness of Tread	D60
KG	Load Capacity (kg)	100
KG X4	Max Load Capacity of 4 Castors	300
() () () () () () () () () ()	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
**	Plate Hole Diameter	8
٥	Product Type	Top Plate Castors
<u>\$</u>	Swivel Radius	84
₹	Swivel Radius Temperature Range	-40 min to +80 max
1	Temperature Range	-40 min to +80 max
1	Temperature Range Thread Material	-40 min to +80 max
	Temperature Range Thread Material Total Castor Height	-40 min to +80 max No 108
<u>I</u> <u>I</u> <u> </u>	Temperature Range Thread Material Total Castor Height Tread Width (mm)	-40 min to +80 max No 108
	Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	-40 min to +80 max No 108 30 White Polyamide
	Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	-40 min to +80 max No 108 30 White Polyamide Maroon

Dimensions





