





















80mm Red Polyurethane Swivel Castors with Brake

80-3360-PNB/SWB MAROON

This 80mm braked polyurethane castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swivel braked castor, with the polyurethane wheel is strong and durable and suitable for moving machinery and equipment. The polyurethane tire is bonded onto the polyamide nylon centre making the castor strong and durable. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D60
	Load Capacity (kg)	100
	Max Load Capacity of 4 Castors	300
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	123
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	108
	Tread Width (mm)	30
	Wheel Centre	White Polyamide
	Wheel Colour	Maroon
	Wheel Diameter(mm)	80
	Wheel Material	Polyurethane

Dimensions

