

80mm Grey Polyurethane Swivel Castor with Brake - 7871389

80-3360-PNB/SWB

This 80mm braked polyurethane castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swivel braked castor with the grey polyurethane wheel is strong and durable and suitable for moving machinery and equipment. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

٥	Bearing Type	Roller
50	Colour	No
0	Hardness of Tread	D60
KG	Load Capacity (kg)	150
	Manufacturer Part No.	TSZ7 NPR 080/30 P2 BP
KG X4	Max Load Capacity of 4 Castors	450
	Plate Dimension Length (mm)	105
2 1	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
N.	Plate Hole Diameter	8
٥	Product Type	Top Plate Castors
© 0	Product Type Swivel Radius	Top Plate Castors
₫	Swivel Radius	123
	Swivel Radius Temperature Range	123 -40 min to +80 max
	Swivel Radius Temperature Range Thread Material	123 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	123 -40 min to +80 max No 108
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	123 -40 min to +80 max No 108
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	123 -40 min to +80 max No 108 38 Grey Polyamide
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	123 -40 min to +80 max No 108 38 Grey Polyamide Grey

Dimensions





