

## 80mm High Temperature Castors with Brake & Phenolic Resin Wheel 80-3360-TH/SWB


This 80mm medium duty swivel top plate braked castors with a termotex phenolic resin wheel suitable for medium/heavy duty applications, medical equipment, catering equipment and food manufacturing trolleys. The zinc plated castors are strong and durable and the termotex phenolic resin wheels are resistant to temperatures from -40C to +280C maximum. The foot operated brake simultaneously brakes both the swivel head and the wheel.




## **Technical Specifications**

Õ	Bearing Type	Plain
5	Colour	No
0	Hardness of Tread	D85
KG	Load Capacity (kg)	100
×g ×4	Max Load Capacity of 4 Castors	300
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80
	Plate Hole Centres Width (mm)	60
*	Plate Hole Diameter	8
Õ	Product Type	Top Plate Castors
19 19	Product Type Swivel Radius	Top Plate Castors
5	Swivel Radius	120
	Swivel Radius Temperature Range	120 -40 min to + 280 max
	Swivel Radius Temperature Range Thread Material	120 -40 min to + 280 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	120 -40 min to + 280 max No 108
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	120 -40 min to + 280 max No 108 35
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	120 -40 min to + 280 max No 108 35 Black Phenolic Resin

## Dimensions







Email: sales@rosscastors.co.uk

Ross Handling 1 Tuxford Road Leicester LE4 9TZ