


















JA 100mm Medium Duty Jacking Castor White Nylon Wheel 150kg Load

JA4-100-NYB

This medium duty jacking castor with a 100mm nylon wheel can lift loads an additional 76mm in vertical height. With a side mounted attachment plate jacking castors can be used on a variety of equipment and machinery that require vertical movement as well as horizontal. The jacking operation is achieved by a hexagonal spanner at the top of the jacking unit.



Technical Specifications

	Bearing Type	Roller
	Bolt Hole Size (mm)	10
	Colour	No
	Jacking Unit Extension Height Max 76m	414
	Jacking Unit Height From Plate Lower Bolt Hole	187
	Load Capacity (kg)	150
	Max Load Capacity for 2 Jacking Castors	150
	Min Jacking Unit Extension Height	338
	Operating Method	24mm Spanner
	Plate Dimension Length (mm)	130
	Plate Dimension Width (mm)	75
	Plate Hole Centres Length (mm)	102
	Plate Hole Centres Width (mm)	51
	Plate Hole Diameter	11
	Product Type	Jacking Castors
	Swivel Radius	178
	Technical PDF	JA4-100-NYB.pdf
	Thread Material	No
	Total Castor Height	128 + 76
	Total Height to Plate Lower Bolt Hole	151
	Tread Width (mm)	35
	Wheel Centre	White Polyamide
	Wheel Colour	White
	Wheel Diameter(mm)	100
	Wheel Material	Nylon

Dimensions

