








JA 100mm Medium Duty Jacking Castor with Brake Polyurethane Wheel 150kg Load

JA4-100-PNB/SWB

This medium duty jacking castor with a brake and a 100mm polyurethane wheel can lift loads an additional 76mm in vertical height. With a side mounted attachment plate jacking castors can be used on a variety of equipment and machinery that require vertical movement as well as horizontal. The jacking operation is achieved by a hexagonal spanner at the top of the jacking unit. The foot operated brake will brake the castor swivel head and wheel.



Technical Specifications

| | | |
|---|--|-----------------|
|  | Bearing Type | Roller |
|  | Bolt Hole Size (mm) | 10 |
|  | Colour | No |
| | Jacking Unit Extension Height Max 76m | 414 |
| | Jacking Unit Height From Plate Lower Bolt Hole | 187 |
|  | Load Capacity (kg) | 150 |
| | Max Load Capacity for 2 Jacking Castors | 150 |
| | Min Jacking Unit Extension Height | 338 |
| | Operating Method | 24mm Spanner |
|  | Plate Dimension Length (mm) | 130 |
|  | Plate Dimension Width (mm) | 75 |
|  | Plate Hole Centres Length (mm) | 102 |
|  | Plate Hole Centres Width (mm) | 51 |
|  | Plate Hole Diameter | 11 |
|  | Product Type | Jacking Castors |
|  | Swivel Radius | 327 |
|  | Thread Material | No |
|  | Total Castor Height | 128 + 76 |
| | Total Height to Plate Lower Bolt Hole | 151 |
|  | Tread Width (mm) | 30 |
|  | Wheel Centre | White Polyamide |
|  | Wheel Colour | Maroon |
|  | Wheel Diameter(mm) | 100 |
|  | Wheel Material | Polyurethane |

Dimensions

