



















Heavy Duty Jacking Castor with Polyurethane 125mm Wheel 200mm Lift RH6-125-SUB

This heavy duty jacking castor with a 125mm heavy duty polyurethane wheel can lift loads an additional 200mm in vertical height. These ingenious jacking castors have a side mounted plate for attachment and a crank handle for ease of lifting movement.



Technical Specifications

	Bearing Type	Roller
	Bolt Hole Size (mm)	10
	Colour	No
	Jacking Unit Extension Height Max 200mm	774
	Jacking Unit Height From Plate Lower Bolt Hole	339
	Load Capacity (kg)	550
	Max Load Capacity for 2 Jacking Castors	550
	Min Jacking Unit Extension Height	574
	Operating Method	Handle
	Plate Dimension Length (mm)	150
	Plate Dimension Width (mm)	100
	Plate Hole Centres Length (mm)	110
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	11
	Product Type	Jacking Castors
	Swivel Radius	108
	Thread Material	No
	Total Castor Height	164 + 200
	Total Height to Plate Lower Bolt Hole	235
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

Dimensions

