




















RH 160mm Heavy Duty Jacking Castor with a 200mm lift with a swivel rubber wheel and brake

RH6-160-HRT/SWB

This heavy duty jacking castor with a brake and a 160mm heavy duty rubber wheel can lift loads an additional 200mm in vertical height. These ingenious jacking castors have a side mounted plate for attachment and a crank handle for ease of lifting movement. The foot operated brake will brake the castor swivel head and wheel.



Technical Specifications

	Bearing Type	Ball Journal
	Bolt Hole Size (mm)	10
	Colour	No
	Jacking Unit Extension Height Max 200mm	810
	Jacking Unit Height From Plate Lower Bolt Hole	339
	Load Capacity (kg)	300
	Max Load Capacity for 2 Jacking Castors	300
	Min Jacking Unit Extension Height	610
	Operating Method	Handle
	Plate Dimension Length (mm)	150
	Plate Dimension Width (mm)	100
	Plate Hole Centres Length (mm)	110
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	11
	Product Type	Jacking Castors
	Swivel Radius	125
	Thread Material	No
	Total Castor Height	200 + 200
	Total Height to Plate Lower Bolt Hole	271
	Tread Width (mm)	50
	Wheel Centre	Cast iron
	Wheel Colour	Black
	Wheel Diameter(mm)	160
	Wheel Material	Rubber

Dimensions

