



















RH 200mm Heavy Duty Jacking Castor with a 200mm lift and a swivel rubber wheel

RH8-200-HRT

This heavy duty jacking castor with a 200mm heavy duty rubber wheel can lift loads an additional 200mm in vertical height. These ingenious jacking castors have a side mounted plate for attachment and a crank handle for ease of lifting movement.



Technical Specifications

	Bearing Type	Ball journal
	Bolt Hole Size (mm)	10
	Colour	No
	Jacking Unit Extension Height Max 200m	850
	Jacking Unit Height From Plate Lower Bolt Hole	339
	Load Capacity (kg)	450
	Max Load Capacity for 2 Jacking Castors	450
	Min Jacking Unit Extension Height	650
	Operating Method	Handle
	Plate Dimension Length (mm)	150
	Plate Dimension Width (mm)	100
	Plate Hole Centres Length (mm)	110
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	11
	Product Type	Jacking Castors
	Swivel Radius	154
	Thread Material	No
	Total Castor Height	240 + 200
	Total Height to Plate Lower Bolt Hole	311
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Black
	Wheel Diameter(mm)	200
	Wheel Material	Rubber

Dimensions

